

Inline Flow Meter

- Direct Reading
- Mountable in any position
- Cost effective
- PVC and Viton, standard



The scale on the outside of the rotameter tube provides a visual indication of the flow rate as fluid moves through the tube.

The spring actuated, Inline Flow Meter can easily be mounted in any position. Because there are very few working parts, the meter is easy to maintain and clean.

Models:

Small (Water Flow 3-15 GPM)

| | |
|--------|-----------------|
| ½" NPT | #ADS-IFM-1191-4 |
| ¾" NPT | #ADS-IFM-1191-6 |
| 1" NPT | #ADS-IFM-1191-8 |

Large (Water Flow 20-50 GPM)

| | |
|----------|-----------------|
| ¾" NPT | #ADS-IFM-477-6 |
| 1" NPT | #ADS-IFM-477-8 |
| 1 ½" NPT | #ADS-IFM-477-12 |

Applications:

- Cooling Towers
- Process Water
- Wastewater
- Ultra Pure Water
- Aqueous Chemical Solutions

Specifications:

- Max flow ranges: 3 GPM (20 LPM)
50 GPM (200 LPM)
- Process Drop: 4PSI at Full scale flow
- Temperature/Pressure: 200 PSIG at 70° F
100 PSIG at 100° F
- Optional Electrical Switches and Materials of Construction are available