



# MODEL VR6

GAS CHLORINATOR

## -INNOVATION & QUALITY-

The Model VR6 Vacuum Regulator is designed for applications ranging from single-cylinder systems to cylinder automatic switchover systems. Offering the option of an attached meter panel and rate control valve, the VR6 is designed to be a simple, easilymaintained and cost-effective vacuum regulator.

The VR6 is available for use with Chlorine or Sulfur Dioxide & for feed capacities up to 500 PPD (10 kg/hr). The VR6 is available for use on upright (150lb) cylinders or ton containers (with one of the ton container adapters manufactured by Archer Instruments). The VR6 incorporates:

- a simple, reliable empty-tank indicator
- built-in relief (vent) valve
- (optional) attached meter panel & rate valve (100 PPD & below only)



Shown above: VR6-10C

### What sets the VR6 apart?

- -Solid all-machined construction, using only high quality materials: PVDF Inlet Capsule, Silver Inlet Valve, Tantalum Springs, PVDF Guide Pin. \*Optional Metal Inlet Capsule.
- -The VR6 is designed with the fewest parts of any vacuum regulator!
- -Easily removable inlet filter cartridge & porous PTFE (Teflon) filter (≤100 PPD)
- -3-year warranty and the most comprehensive list of lifetime-warranty parts: front body, back body, inlet capsule, inlet spring, vent spring & diaphragm

Vacuum Tubing (LDPE tubing)			
Model #	Capacity	Vacuum	Vent Tubing
		Tubing	
VR6-10X	100 PPD (2KG/hr)	3/8" OD	3/8" OD
VR6-25X	250 PPD (5KG/hr)	1/2" OD	3/8" OD
VR6-50X	500 PPD (10 KG/hr)	5/8" OD	3/8" OD
"X" = $\underline{\mathbf{C}}$ - Chlorine / $\underline{\mathbf{S}}$ -Sulfur Dioxide			



#### **VR6 Materials of Construction**

PVC, PVDF (Kynar), PTFE (Teflon), Monel, Tantalum, Silver, FKM (Viton)

635A Twisted Wrench

## **Options & Related Products Available From Archer Instruments**



#### With MPA-60X Meter Panel

• Accuracy: +/- 4% of scale

• Turndown: 20:1



SMA-10X Switchover Module



EOA-10X Ejector



TCA-MONEL Ton Container Adapter