

Gravity Flow Tablet Feeders



LF Series Tablet Feeders

- Potable water or wastewater
- Four models to choose from
- Flow rates 500 GPD to 400,000 GPD



Series 2000 and 4000 Tablet Feeders

- Adjustable baffles, weirs, or outlet sluice
- Five different models available
- Available with minimum flow from 200 – 200,000 and maximum flow from 100,000 – 400,000 GPD



Tri-Max Tablet Feeders

- Chlorinate or dechlorinate up to 275 GPM
- Potable water or wastewater
- Placed directly in the effluent stream
- Portable Unit OR permanently installed



Tab-Le-Kit

Simple, quick installation

Includes: Tablet Feeder, piping, 3-way bypass valve, chlorine test strips (free or total).

Used for: small villages, remote hospitals, camps, parks, or rest stops.

Chlorine & De-chlor Tablets

Chlorine
Calcium Hypo Chlorite



Bio-Sanitizer

70% Chlorine
Available in 10, 25,
45, & 100 lb pails

De-Chlorination
Sodium Sulfite

Bio-Neutralizer



35% Sodium Sulfite
Available in 25 or 45
lb pails

Bio-Max



92% Sodium Sulfite
48 lb pail

Residential
Wastewater Treatment

Non-Hazardous



Disinfecting Tablets
8 Pack – 1.9 lb pail